

















# LED Profil MFL | max. LED Leistung pro Meter: 48W → 1 x Flexstrip 160 oder 2 x Flexstrip 108

ALUMINIUM PROFILE & ABDECKUNGEN   ALUMINIUM PROFILES & COVERS	
  <p><b>AP-005-005</b> Natur eloxiert   Natural anodized  <b>AP-005-105</b> Schwarz eloxiert   Black anodized                  Aluminium Profil MFL   Aluminium profile MFL</p>	  <p><b>AB-005-100</b>                  Aluminium Abdeckung MF                  Aluminium cover MF</p>

PROFIL ABDECKUNGEN UND EINSCHÜBE   PROFILE COVERS AND INSETS			
<p><math>\eta \approx 79\%</math></p>   <p><b>AB-005-001</b>                  PMMA Abdeckung                  MF Flach Transparent                  PMMA cover                  MF flat transparent</p>	<p><math>\eta \approx 64\%</math></p>   <p><b>AB-005-003</b>                  PMMA Abdeckung                  MF Flach Opal                  PMMA cover                  MF flat milky</p>	<p><math>\eta \approx 73\%</math></p>   <p><b>AB-005-006</b>                  PMMA Abdeckung                  MF Rund Opal                  PMMA cover                  MF round milky</p>	
<p><math>\eta \approx 72\%</math></p>   <p><b>AB-005-009</b>                  PMMA Abdeckung                  MF Eckig Opal                  PMMA cover                  MF square milky</p>	<p><math>\eta \approx 67\%</math></p> <p>Transparente Abdeckung erforderlich                  Transparent cover necessary</p>   <p><b>MP-005-001</b>                  Mikroprism. Einschub                  MF Transparent                  Microprismatic Inset                  MF transparent</p>	<p><math>\eta \approx 65\%</math></p> <p>Transparente Abdeckung erforderlich                  Transparent cover necessary</p>   <p><b>MP-005-003</b>                  Mikroprism. Einschub                  MF Opal                  Microprismatic Inset                  MF milky</p>	

PROFIL ENDKAPPEN   PROFILE ENDCAPS		
<p>Endkappenstärke   End cap thickness 2,5mm</p>  <p><b>EK-005-500</b> Natur eloxiert   Natural anodized  <b>EK-105-500</b> Schwarz eloxiert   Black anodized                  MFL Flach geschlossen   MFL flat closed</p>	<p>Endkappenstärke   End cap thickness 2,5mm</p>  <p><b>EK-005-510</b>                  Profil Endkappe MFL Rund geschlossen                  Profile endcap MFL round closed</p>	<p>Endkappenstärke   End cap thickness 2,5mm</p>  <p><b>EK-005-520</b>                  Profil Endkappe MFL Eckig geschlossen                  Profile endcap MFL square closed</p>

1m	2m	4m	SONDER LÄNGE	SPECIAL LENGTH
----	----	----	--------------	----------------

STANDARDLÄNGE = 2M | ALLE ANDEREN LÄNGEN SIND VOM UMTAUSCH UND DER RÜCKGABE AUSGESCHLOSSEN. LÄNGEN ÜBER 2M WERDEN MITTELS SPEDITION VERSENDET UND ERFORDERN EINE MINDESTBESTELLMENGE VON 10 STK.

STANDARD LENGTH = 2M | ALL OTHER LENGTHS ARE EXCLUDED FROM EXCHANGE AND RETURN. LENGTHS OVER 2M ARE SHIPPED BY FREIGHT CARRIER AND REQUIRE A MINIMUM ORDER QUANTITY OF 10 PCS.

## HINWEIS PLEASE NOTE






Kunststoff und Aluminium besitzen unterschiedliche Ausdehnungskoeffizienten, welche bei der Montage zu berücksichtigen sind. Ausgehend von 20°C verändert sich die Länge beim Aluminium um ca. 0,25mm pro Meter und beim Kunststoff um ca. 0,70mm pro Meter je 10°C Temperaturunterschied.

Plastic and aluminium have different expansion coefficients, which must be considered during assembly. Based on 20°C the length of aluminium changes approximately 0,25mm per meter and plastic approximately 0,70 mm per meter per 10°C of difference in temperature.






# LED Profile MFL | max. LED power per meter: 48W → 1 x Flexstrip 160 or 2 x Flexstrip 108

PROFIL ZUBEHÖR   PROFILE ACCESSORIES		
 <p><b>PZ-001-002</b> Seilabhänger 2m inkl. Deckenbefestigung Wire suspension 2m incl. ceiling fixture</p> <p><b>PZ-001-005</b> Seilabhänger 5m inkl. Deckenbefestigung Wire suspension 5m incl. ceiling fixture</p>	 <p><b>PZ-002-001</b> Seilstopper inkl. M4 Senkkopfschraube Wire stopper incl. M4 countersunk screw</p>	 <p><b>EK-100-002</b> Torx Bit TX8 für Endkappenschrauben Torx Bit TX8 for endcap screws</p>
 <p><b>PZ-006-001</b> Saugnapf 30mm Suction cup 30mm</p>		






## MFL PROFIL BESTÜCKT MIT 2 X FLEXSTRIP 36 RGB MIT EINEM LED ABSTAND VON 33MM IN KOMBINATION MIT DEN UNTERSCHIEDLICHEN ABDECKUNGEN MFL PROFILE FITTED WITH 2 X FLEXSTRIP 36 RGB WITH A LED DISTANCE OF 33MM IN COMBINATION WITH THE DIFFERENT COVERS

<p>PMMA Abdeckung MF Flach Transparent 91% Transmission</p> 	<p>PMMA Abdeckung MF Flach Transp. 91% Transmission + Mikroprismatik Transp. 95% Transmission</p> 	<p>PMMA Abdeckung MF Flach Transp. 91% Transmission + Mikroprismatik Opal 93% Transmission</p> 	<p>PMMA Abdeckung MF Flach Opal 76% Transmission</p> 	<p>PMMA Abdeckung MF Eckig Opal 76% Transmission</p> 
<p>PMMA cover MF flat transparent 91% transmission</p>	<p>PMMA cover MF flat transparent 91% transmission + Microprismatic transparent 95% transmission</p>	<p>PMMA cover MF flat transparent 91% transmission + Microprismatic milky 93% transmission</p>	<p>PMMA cover MF flat milky 76% transmission</p>	<p>PMMA cover MF square milky 76% transmission</p>

## MFL PROFIL BESTÜCKT MIT 2 X FLEXSTRIP 72 MIT EINEM LED ABSTAND VON 16,5MM IN KOMBINATION MIT DEN UNTERSCHIEDLICHEN ABDECKUNGEN MFL PROFILE FITTED WITH 2 X FLEXSTRIP 72 WITH A LED DISTANCE OF 16,5MM IN COMBINATION WITH THE DIFFERENT COVERS

<p>PMMA Abdeckung MF Flach Transparent 91% Transmission</p> 	<p>PMMA Abdeckung MF Flach Transp. 91% Transmission + Mikroprismatik Transp. 95% Transmission</p> 	<p>PMMA Abdeckung MF Flach Transp. 91% Transmission + Mikroprismatik Opal 93% Transmission</p> 	<p>PMMA Abdeckung MF Flach Opal 76% Transmission</p> 	<p>PMMA Abdeckung MF Eckig Opal 76% Transmission</p> 
<p>PMMA cover MF flat transparent 91% transmission</p>	<p>PMMA cover MF flat transparent 91% transmission + Microprismatic transparent 95% transmission</p>	<p>PMMA cover MF flat transparent 91% transmission + Microprismatic milky 93% transmission</p>	<p>PMMA cover MF flat milky 76% transmission</p>	<p>PMMA cover MF square milky 76% transmission</p>

## MFL PROFIL BESTÜCKT MIT 2 X FLEXSTRIP 48 ODER 72 DW MIT EINEM LED ABSTAND VON 7,15MM IN KOMBINATION MIT DEN UNTERSCH. ABDECKUNGEN MFL PROFILE FITTED WITH 2 X FLEXSTRIP 48 OR 72 DW WITH A LED DISTANCE OF 7,15MM IN COMBINATION WITH THE DIFFERENT COVERS

<p>PMMA Abdeckung MF Flach Transparent 91% Transmission</p> 	<p>PMMA Abdeckung MF Flach Transp. 91% Transmission + Mikroprismatik Transp. 95% Transmission</p> 	<p>PMMA Abdeckung MF Flach Transp. 91% Transmission + Mikroprismatik Opal 93% Transmission</p> 	<p>PMMA Abdeckung MF Flach Opal 76% Transmission</p> 	<p>PMMA Abdeckung MF Eckig Opal 76% Transmission</p> 
<p>PMMA cover MF flat transparent 91% transmission</p>	<p>PMMA cover MF flat transparent 91% transmission + Microprismatic transparent 95% transmission</p>	<p>PMMA cover MF flat transparent 91% transmission + Microprismatic milky 93% transmission</p>	<p>PMMA cover MF flat milky 76% transmission</p>	<p>PMMA cover MF square milky 76% transmission</p>