

# LED Profil SLA | max. LED Leistung pro Meter: 55W → 3 x Flexstrip 75 oder 2 x Flexstrip 108

| ALUMINIUM PROFILE & ABDECKUNGEN   ALUMINIUM PROFILES & COVERS   |  |
|---|--|
| <p><b>AP-003-002</b> Natur eloxiert   Natural anodized<br/> <b>AP-003-102</b> Schwarz eloxiert   Black anodized<br/>                 Aluminium Profil SLA   Aluminium profile SLA</p> | <p><b>AB-003-100</b><br/>                 Aluminium Abdeckung SL<br/>                 Aluminium cover SL</p> |

| PROFIL ABDECKUNGEN UND EINSCHÜBE   PROFILE COVERS AND INSETS  |  |   |
|---|--|---|
| <p><math>\eta \approx 73\%</math></p> <p><b>AB-003-001</b><br/>                 PMMA Abdeckung<br/>                 SL Flach Transparent<br/>                 PMMA cover<br/>                 SL flat transparent</p> | <p><math>\eta \approx 60\%</math></p> <p><b>AB-003-003</b><br/>                 PMMA Abdeckung<br/>                 SL Flach Opal<br/>                 PMMA cover<br/>                 SL flat milky</p>   | <p><math>\eta \approx 64\%</math></p> <p><b>AB-003-006</b><br/>                 PMMA Abdeckung<br/>                 SL Rund Opal<br/>                 PMMA cover<br/>                 SL round milky</p>  |
| <p><math>\eta \approx 66\%</math></p> <p><b>AB-003-009</b><br/>                 PMMA Abdeckung<br/>                 SL Eckig Opal<br/>                 PMMA cover<br/>                 SL square milky</p>            | <p>Transparente Abdeckung erforderlich<br/>                 Transparent cover necessary</p> <p><math>\eta \approx 64\%</math></p> <p><b>MP-003-001</b><br/>                 Mikroprism. Einschub<br/>                 SL Transparent<br/>                 Microprismatic Inset<br/>                 SL transparent</p> | <p>Transparente Abdeckung erforderlich<br/>                 Transparent cover necessary</p> <p><math>\eta \approx 61\%</math></p> <p><b>MP-003-003</b><br/>                 Mikroprism. Einschub<br/>                 SL Opal<br/>                 Microprismatic Inset<br/>                 SL milky</p> |

| PROFIL ENDKAPPEN   PROFILE ENDCAPS  |  |  |
|---|--|--|
| <p>Endkappenstärke   End cap thickness 2,5mm</p> <p><b>EK-003-200</b> Natur eloxiert   Natural anodized<br/> <b>EK-103-200</b> Schwarz eloxiert   Black anodized<br/>                 SLA Flach geschlossen   SLA flat closed</p> | <p>Endkappenstärke   End cap thickness 2,5mm</p> <p><b>EK-003-210</b><br/>                 Profil Endkappe SLA Rund geschlossen<br/>                 Profile endcap SLA round closed</p> | <p>Endkappenstärke   End cap thickness 2,5mm</p> <p><b>EK-003-220</b><br/>                 Profil Endkappe SLA Eckig geschlossen<br/>                 Profile endcap SLA square closed</p> |

|  |  |  |
|--|--|--|
| <p>Netzteile mit max. 52mm Breite und 32mm Höhe im Profil integrierbar</p> <p>Aluminium Abdeckung SL erforderlich!</p> |  | <p>Power Supplies with max. 52mm width and 32mm height profile integrable</p> <p>aluminum cover SL required!</p> |
|--|--|--|

|    |    |    |              |                |
|----|----|----|--------------|----------------|
| 1m | 2m | 4m | SONDER LÄNGE | SPECIAL LENGTH |
|----|----|----|--------------|----------------|

STANDARDLÄNGE = 2M | ALLE ANDEREN LÄNGEN SIND VOM UMTAUSCH UND DER RÜCKGABE AUSGESCHLOSSEN. LÄNGEN ÜBER 2M WERDEN MITTELS SPEDITION VERSENDET UND ERFORDERN EINE MINDESTBESTELLMENGE VON 10 STK.

STANDARD LENGTH = 2M | ALL OTHER LENGTHS ARE EXCLUDED FROM EXCHANGE AND RETURN. LENGTHS OVER 2M ARE SHIPPED BY FREIGHT CARRIER AND REQUIRE A MINIMUM ORDER QUANTITY OF 10 PCS.






## HINWEIS PLEASE NOTE

Kunststoff und Aluminium besitzen unterschiedliche Ausdehnungskoeffizienten, welche bei der Montage zu berücksichtigen sind. Ausgehend von 20 °C verändert sich die Länge beim Aluminium um ca. 0,25mm pro Meter und beim Kunststoff um ca. 0,70mm pro Meter je 10 °C Temperaturunterschied.






Plastic and aluminium have different expansion coefficients, which must be considered during assembly. Based on 20 °C the length of aluminium changes approximately 0,25mm per meter and plastic approximately 0,70 mm per meter per 10 °C of difference in temperature.

| PROFIL ZUBEHÖR   PROFILE ACCESSORIES   |   |   |
|--|---|---|
|  <p><b>PZ-001-002</b> 2m Vernickelt   nickelplated<br/> <b>PZ-001-005</b> 5m Vernickelt   nickelplated<br/> <b>PZ-101-002</b> 2m Schwarz   Black<br/>                 Seilabhänger inkl. Deckenbefestigung<br/>                 Wire suspension incl. ceiling fixture</p> |  <p><b>PZ-002-001</b> Vernickelt   nickelplated<br/> <b>PZ-102-001</b> Schwarz   Black<br/>                 Seilstopper inkl. M4 Senkkopfschraube<br/>                 Wire stopper incl. M4 countersunk screw</p> |  <p><b>EK-100-002</b><br/>                 Torx Bit TX8 für Endkappenschrauben<br/>                 Torx Bit TX8 for endcap screws</p>  <p><b>PZ-006-001</b><br/>                 Saugnapf 30mm<br/>                 Suction cup 30mm</p> |






**SLA PROFIL BESTÜCKT MIT 2 X FLEXSTRIP 72 MIT EINEM LED ABSTAND VON 16,5MM IN KOMBINATION MIT DEN UNTERSCHIEDLICHEN ABDECKUNGEN**  
 SLA PROFILE FITTED WITH 2 X FLEXSTRIP 72 WITH A LED DISTANCE OF 16.5MM IN COMBINATION WITH THE DIFFERENT COVERS

| PMMA Abdeckung<br>SL Flach Transparent<br>91% Transmission                        | PMMA Abdeckung SL Flach<br>Transp. 91% Transmission +<br>Mikroprismatik Transp.<br>95% Transmission    | PMMA Abdeckung SL Flach<br>Transp. 91% Transmission +<br>Mikroprismatik Opal<br>93% Transmission | PMMA Abdeckung<br>SL Flach Opal<br>76% Transmission                                 | PMMA Abdeckung<br>SL Eckig Opal<br>76% Transmission                                  |
|---|--|--|---|--|
|  |                      |                |  |  |
| PMMA cover<br>SL flat transparent<br>91% transmission                             | PMMA cover SL flat<br>transparent 91% transmission +<br>Microprismatic transparent<br>95% transmission | PMMA cover SL flat<br>transparent 91% transmission +<br>Microprismatic milky<br>93% transmission | PMMA cover<br>SL flat milky<br>76% transmission                                     | PMMA cover<br>SL square milky<br>76% transmission                                    |

**SLA PROFIL BESTÜCKT MIT 3 X FLEXSTRIP 72 MIT EINEM LED ABSTAND VON 16,5MM IN KOMBINATION MIT DEN UNTERSCHIEDLICHEN ABDECKUNGEN**  
 SLA PROFILE FITTED WITH 3 X FLEXSTRIP 72 WITH A LED DISTANCE OF 16.5MM IN COMBINATION WITH THE DIFFERENT COVERS

| PMMA Abdeckung<br>SL Flach Transparent<br>91% Transmission                         | PMMA Abdeckung SL Flach<br>Transp. 91% Transmission +<br>Mikroprismatik Transp.<br>95% Transmission    | PMMA Abdeckung SL Flach<br>Transp. 91% Transmission +<br>Mikroprismatik Opal<br>93% Transmission | PMMA Abdeckung<br>SL Flach Opal<br>76% Transmission                                  | PMMA Abdeckung<br>SL Eckig Opal<br>76% Transmission                                   |
|--|--|--|--|---|
|  |                     |               |  |  |
| PMMA cover<br>SL flat transparent<br>91% transmission                              | PMMA cover SL flat<br>transparent 91% transmission +<br>Microprismatic transparent<br>95% transmission | PMMA cover SL flat<br>transparent 91% transmission +<br>Microprismatic milky<br>93% transmission | PMMA cover<br>SL flat milky<br>76% transmission                                      | PMMA cover<br>SL square milky<br>76% transmission                                     |

**SLA PROFIL BESTÜCKT MIT 2 X FLEXSTRIP 48 ODER 72 DW MIT EINEM LED ABSTAND VON 7,15MM IN KOMBINATION MIT DEN UNTERSCH. ABDECKUNGEN**  
 SLA PROFILE FITTED WITH 2 X FLEXSTRIP 48 OR 72 DW WITH A LED DISTANCE OF 7.15MM IN COMBINATION WITH THE DIFFERENT COVERS

| PMMA Abdeckung<br>SL Flach Transparent<br>91% Transmission                         | PMMA Abdeckung SL Flach<br>Transp. 91% Transmission +<br>Mikroprismatik Transp.<br>95% Transmission    | PMMA Abdeckung SL Flach<br>Transp. 91% Transmission +<br>Mikroprismatik Opal<br>93% Transmission | PMMA Abdeckung<br>SL Flach Opal<br>76% Transmission                                  | PMMA Abdeckung<br>SL Eckig Opal<br>76% Transmission                                   |
|--|--|--|--|---|
|  |                     |               |  |  |
| PMMA cover<br>SL flat transparent<br>91% transmission                              | PMMA cover SL flat<br>transparent 91% transmission +<br>Microprismatic transparent<br>95% transmission | PMMA cover SL flat<br>transparent 91% transmission +<br>Microprismatic milky<br>93% transmission | PMMA cover<br>SL flat milky<br>76% transmission                                      | PMMA cover<br>SL square milky<br>76% transmission                                     |