

LED Zigbee RF Controller 4 Kanal | LED Zigbee RF controller 4 channel

Mit dem LED Zigbee RF Controller 4 Kanal, können LED Systeme mittels Zigbee Gateway und Tuya APP über Handy und Tablet, Zigbee Bedienstellen aber auch über Sprachdienste wie Alexa gesteuert werden. Zusätzlich gibt es eine Funkfernbedienung und ein Funktouchpanel. Der Controller kann Mono-, Dim-to-Warm-, TW- (Tuneable White), RGB- sowie RGBW- bzw. RGB+W-LEDs ansteuern. Es können bis zu 6 verschiedene Zonen erstellt und das System mithilfe zusätzlicher Controller bzw. auch Zigbee Gateways problemlos skaliert werden.

With the LED Zigbee RF Controller 4 Channel, LED systems can be controlled via Zigbee Gateway and Tuya APP via mobile phone and tablet, Zigbee control points and also via voice services such as Alexa. There is also a radio remote control and a radio touch panel. The controller can control mono, dim-to-warm, TW (tunable white), RGB and RGBW or RGB+W LEDs. Up to 6 different zones can be created and the system can be easily scaled using additional controllers or Zigbee gateways.

Ø72.5 x 25.5mm
0.068kg



LC-022-000

Wifi Zigbee Gateway inkl. 1m USB Kabel
Wifi Zigbee Gateway incl. 1m USB cable

179 x 56.5 x 30mm
0.128kg



LC-022-001

LED Zigbee RF Controller 4 Kanal
12-48VDC | 4x5A (12- 24VDC) | 4x4A (36-48VDC)
LED Zigbee RF Controller 4 Channel
12-48VDC | 4x5A (12-24VDC) | 4x4A (36-48VDC)

141 x 50 x 19mm
0.074kg



LC-022-002

LED Zigbee RF Fernbedienung All in One
LED Zigbee RF remote control all in one

86 x 86 x 33 mm (12mm Aussen | Outside)
0.185kg



LC-022-003

LED Zigbee RF Touchpanel All in One mit 230VAC
LED Zigbee RF touch panel all in one with 230VAC

PRODUKTSPEZIFIKATIONEN PRODUCT SPECIFICATIONS

Dimmbereich | Dimming range: 1-100%

PWM Frequenz | PWM Frequency: 500Hz, 2.000Hz, 8.000Hz, 16.000Hz

Ausblendzeit | Fading time: 0.5s, 1s, 2s, 3s

Eingangssignal | Input signal: Zigbee, RF 2.4 Ghz, Push-DIM (potentialfrei | potential-free)

Dimmstufen | Dimming scale: 4096

Max. Leitungsquerschnitt | Max. Wire cross-section: 2,5mm²

Controller Abmessungen | Controller size: 179 x 56.5 x 30mm

Controller Gewicht | Controller weight: 0.188kg

Zustand nach Netzzurückkehr | Status after mains return: Zuletzt eingestellter Wert | Last select value



Werkzeuglose Montage der Anschlusskabeln
mittel Schnappklemmen!
Tool-free assembly of the connecting cables
medium snap clamps!



Preis & Verfügbarkeit
Price and Availability



Anschlusssschema
Connection diagram



Bedienungsanleitung
Instruction manual



Montagerichtlinien
Assembly guidelines



Weitere Informationen mittels QR Code
Further information via QR code